

Product data sheet

Characteristics

56RCLE-GY

Residual current circuit breaker, Clipsal - 56 Series, 2P, 20 A, 30 mA, 250 V



Main

Range	Clipsal - 56 Series
Product or component type	Residual current circuit breaker (RCCB)
Product brand	Clipsal
Device application	Protection
Poles description	2P
[In] rated current	20 A
Earth-leakage sensitivity	30 mA

Complementary

[Ue] rated operational voltage	250 V AC 50 Hz
Control type	Push-button
Protection type	Earth-leakage protection
Installation direction	Vertical
Mounting mode	Surface mounted
Mounting support	DIN rail
Size	107 x 101 x 101 mm conforming to DIN 43880
Height	101 mm
Width	101 mm
Depth	65 mm
Net weight	0.3 kg
Colour	Grey (RAL 7035)
Material	Polycarbonate
Number of gangs	1 gang
Cable cross section	1...10 mm ²

Environment

IP degree of protection	IP66
Ambient air temperature for operation	-25...75 °C

Offer Sustainability

EU RoHS Directive	Compliant  EU RoHS Declaration
-------------------	---

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.